L Number	Hits	Search Text	DB	Time stamp
3	10	(electrotherapy or electrostimulation or	EPO; JPO;	2003/11/28 09:32
		kinestherapy or kinesiotherapy) AND (led	DERWENT	
		or ped or light AND emitting AND diode or		
1		laser AND emitting AND diode or laser AND		
1		diode or light AND diode or photon AND		
		diode or photon AND emitting AND diode or		
		photo AND emitting AND diode or photo AND		ļ
		diode)		
4	1	("4930505").PN.	EPO; JPO;	2003/11/28 09:32
			DERWENT	

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

	(51) International Patent Classification ⁶ : A61N 5/06		A1	(11) International Publication Number:		WO 99/34868	
				(43	3) International Publication Date:	15 July 1999 (15.07.99)	
	(21) International Application Number:	PCT/US	98/2713	32	(81) Designated States: AL, AM, AT, A	U, AZ, BA, BB, BG, BR,	

(30) Priority Data: 09/003,665

(22) International Filing Date:

7 January 1998 (07.01.98)

18 December 1998 (18.12.98)

US

(71)(72) Applicant and Inventor: SEGAL, Kim, Robin [US/US]; 18902 White Water Lane, Dallas, TX 75287 (US).


(74) Agents: MCCOMBS, David, L. et al.; Haynes and Boone, L.L.P., 3100 NationsBank Plaza, 901 Main Street, Dallas, TX 75202-3789 (US).

PCT/US98/27132 (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: DIODE LASER IRRADIATION AND ELECTROTHERAPY SYSTEM FOR BIOLOGICAL TISSUE STIMULATION



(57) Abstract

The present invention is an irradiation, and electrotherapy system for treating biological tissue of a subject without exposing the tissue to damaging effects. The system includes a manipulable wand (14') for contact with the tissue, a diode laser (52) disposed in the wand for irradiating the tissue with coherent optical energy, a metal sheath (62) for providing electrical stimulation to the tissue, and setting controls for operating the wand to achieve a rate of absorption, a conversion to heat in the irradiated tissue in a range between a minimum rate sufficient to elevate the average temperature of the irradiated tissue to a level above the basal body temperature of the subject, and a maximum rate which is less than the rate at which the irradiated tissue is converted into a collagenous substance.

United States Patent [19]

Hatje

[11] Patent Number:

4,930,505

[45] Date of Patent:

Jun. 5, 1990

[54]		THOI LL-BI			 	 URE
	_		_	 	 	_

[75] Inventor: Guenther H. Hatje, Hamburg, Fed. Rep. of Germany

[73] Assignee: Helmut K. Pinsch GmbH & Co., Hamburg, Fed. Rep. of Germany

[21] Appl. No.: 105,608

[22] Filed: Oct. 5, 1987

[30] Foreign Application Priority Data

Oct. 4, 1986 [EP] European Pat. Off. 86113792.5

[56] References Cited

U.S. PATENT DOCUMENTS

4,564,012	1/1986	Shimada et al	128/395
4,573,465	3/1986	Sugiyama et al	128/395
4.724.835	2/1988	Liss et al 1	28/303.1

FOREIGN PATENT DOCUMENTS


0143185	6/1985	European Pat. Off	
2458272	2/1981	France	128/395
2571264	4/1986	France	128/395
2577425	8/1986	France .	
1102614	7/1984	U.S.S.R	128/395
1242188	7/1986	U.S.S.R	128/395
8606642	11/1986	World Int. Prop. O	

Primary Examiner—Edward M. Coven Assistant Examiner—Mark J. Graham

[57] ABSTRACT

A method of enhancing the well-being of a living creature, wherein energy from a laser light-source bombards a target area on the skin or hide of the living creature, a short-pulsed laser light source is disposed remote from the target area and produces an elevated emergence energy density so that its radiation, for a short duration, applies a high output per unit area to the target area.

8 Claims, 2 Drawing Sheets





United States Patent [19]

Stromer

Patent Number: [11]

5,304,207

Date of Patent:

Apr. 19, 1994

[54] ELECTROSTIMULATOR WITH LIGHT **EMITTING DEVICE**

[76] Inventor: Merrill Stromer, 8924 N. 65th St.,

Paradise Valley, Ariz. 85253

[21] Appl. No.: 831,163

[22] Filed: Feb. 5, 1992

[51] Int. Cl.⁵ A61N 1/00; A61N 1/18; A61N 1/40 607/3; 607/46; [52] U.S. Cl.

607/88; 607/145 [58] Field of Search 128/419 R, 419 S, 419 C, 128/783, 798, 800, 802, 395, 907, 421, 422, 362, 396, 420 R, 420 A, 786, 803, 632-633; 606/32, 42; 600/13, 14; 604/20; 273/84 ES; 361/232,

225; 33/233; 231/7; 607/46, 88, 90

[56] References Cited

U.S. PATENT DOCUMENTS

4.112,923	9/1978	Tomecek	128/419 R·X
4,305,390	12/1981	Swartz	128/362 X
4,486,807	12/1984	Yanez	273/84 ES
4,535,784	8/1985	Rohlicek et al	
4,694,840		Kairis et al	128/907 X
4,763,657		Chen et al	
4.846.044		Lahr	
4.917.092		Todd et al	
4.949.721		Toriu et al	
4.968.034		Hsieh	
		Tannenbaum	
4.989.605		Rossen	
5.024,236		Shapiro	
5,133,352		Lathrop et al	

OTHER PUBLICATIONS

Colov, H. C., "Low Level Laser Biomodulation for Chronic Pain Management," Contemporary Issues in Chronic Pain Management, Kluwer Academic Publishers, 1991, pp. 287-295.

Kleinkort, J. A. and R. A. Foley, "Laser Acupuncture: Its Use in Physical Therapy," American Journal of Acupuncture, vol. 12, No. 1, 1984, pp. 51-56.

Soric, R. and M. Devlin, "Transcutaneous Electrical Nerve Stimulation-Practical Aspects and Applications," Postgraduate Medicine, vol. 78, No. 4, Sep. 15, 1985, pp. 101-106.


Walker, J. "Relief from Chronic Pain by Low Power Laser Irradiation", Neuroscience Letters, vol. 43, 1983, pp. 339-344.

Primary Examiner-Richard J. Apley Assistant Examiner—John P. Leubecker

ABSTRACT

An improved electrostimulator apparatus, comprises first and second electrodes spaced-apart a predetermined distance, an electrical signal generator for providing pulses of predetermined width and repetition rate to the spaced-apart electrodes, and an LED providing a beam of light projecting between the spaced-apart electrodes toward the object intended to be electrostimulated. The electrodes have substantially co-planar external faces approximately perpendicular to the light beam. The electrodes, signal generator and LED are mounted in an elongated housing having a longitudinal central axis. The electrodes are exposed on an end and the light beam is emitted from the same end and substantially parallel to the central axis. An ON/OFF switch actuates the signal generator and the LED when turned ON. It automatically turns OFF state when released so that the signal generator and the LED are always ON or OFF together.

18 Claims, 1 Drawing Sheet



1 Numéro de publication:

0 092 015 A1

12

DEMANDE DE BREVET EUROPEEN

Numéro de dépôt: 82810160.0

(f) Int. Cl.3: A 61 N 1/30, A 61 N 1/08

2 Date de dépôt: 16.04.82


(3) Date de publication de la demande: 26.10.83 Bulletin 83/43 Demandeur: Brodard, Roland, Avenue des Châtaigniers, 4, CH-1844 Villeneuve (CH)

inventeur: Brodard, Roland, Avenue des Châtaigniers, 4, CH-1844 Villeneuve (CH)

Etats contractants désignés: AT BE CH DE FR GB IT LI LU NL SE Mandataire: Steiner, Martin et al, c/o AMMANN INGENIEURS-CONSEILS EN PROPRIETE INTELLECTUELLE SA BERNE Schwarztorstrasse 31, CH-3001 Bern (CH)

Dispositif d'ionisation.

50 Le dispositif comprend un générateur de courant (3, 6) réglable par un potentiomètre (2). Une résistance (11) est connectée en série avec une paire d'électrodes amovibles (10a, 10b) dans un circuit de contre-réaction du générateur par l'intermédiaire d'un transistor (8). La résistance (11) est solidaire des électrodes et détermine l'intensité du courant dans celles-ci. Sa valeur est déterminée par la surface des électrodes pour maintenir constante la densité de courant. Une diode LED (14) associée à un circuit (13) donne une indication de la densité de courant dans les électrodes. Une diode LED (19) associée à un comparateur (16, 17, 18) signale une saturation du transistor (8) limitant le courant lorsque la résistance entre les électrodes dépasse une valeur critique. Un comparateur (21) commandant une diode LED (22) de signalisation de sécurité et un second transistor (24) permettent d'interrompre le courant dans les électrodes si, en raison d'une forte résistance entre ces dernières, la tension sur la résistance (11) tombe en dessous de la tension d'entrée du générateur.



0

ACTORUM AG

DERWENT-ACC-NO:

1983-802599

DERWENT-WEEK:

198344

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE:

Electrotherapeutic ioniser with adjustable current generator - has indicator and responds automatically to current density for safeguard against burns by sounding alarm

INVENTOR: BROADARD, R

PATENT-ASSIGNEE: BRODARD R[BRODI]

PRIORITY-DATA: 1982EP-0810160 (April 16, 1982)

PATENT-FAMILY:

PUB-NO EP 92015 A PUB-DATE

LANGUAGE

PAGES

MAIN-IPC

October 26, 1983

DESIGNATED-STATES: BE CH DE FR GB IT LI NL

CITED-DOCUMENTS: CH 385366; FR 2153191 ; FR 2180666 ; GB 2064178 ; US 4141359

INT-CL (IPC): A61N001/30

ABSTRACTED-PUB-NO: EP 92015A

BASIC-ABSTRACT:

The current generator comprises two operational amplifiers (3,6) with negative feedback loops, one purely resistive (4,5) and the other incorporating a saturable transistor (8) which supplies ionising current to body electrodes (10a,10b). A resistance (11) integral with the pair of electrodes determines the current density which is monitored by an operational amplifier (13) controlling a first LED (144) controlling a first LED (14).

Saturation of the transistor (8) is indicated by a voltage comparator (18) controlling a second LED (19) which gives warning of abnormal increase of resistance between the electrodes. When the voltage across the measuring resistance (11) falls far below a desired value with risk of burning the patient, a safety comparator (21) lights a third LED (22), operates a LED-phototransistor coupler (23) to sound an alarm (30), and closes a short-circuiting transistor switch (24). The circuit is esp. for use with an electrotherapeutic ioniser.

CHOSEN-DRAWING: Dwg.2/3

TITLE-TERMS: ELECTROTHERAPY IONISE ADJUST CURRENT GENERATOR INDICATE RESPOND AUTOMATIC CURRENT DENSITY SAFEGUARD BURN SOUND ALARM

DERWENT-CLASS: P34 S05 EPI-CODES: S05-A04;

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N1983-193361

United States Patent [19]

4,124,030 [11] Nov. 7, 1978 Roberts .[45]

[54]			HERAPEUTIC FARADIC ENERATOR
[76]	Iņve		Vallace A. Roberts, 88 N. Main St. ellingham, Mass. 02019
[21]	Appl	. No.: 7	56,781
[22]	Filed	: J	an. 5, 1977
[52]	U.S.	CI.	
[56]		1	References Cited
		U.S. PA	TENT DOCUMENTS
3,10 3,3	09,430 87,147	10/1963 11/1963 6/1968 10/1973	Tischler 128/42 Radwan 128/422

3,794,022	2/1974	Nawracaj et al 128/420 A X
3,797,500	3/1974	Porter 128/422
3,908,669	9/1975	Man et al 128/422
3,911,930	10/1975	Hagfors et al 128/422 X
3,958,577	5/1975	Rodler 128/420 A

Primary Examiner-Wm. E. Kamm Attorney, Agent, or Firm-William Nitkin

ABSTRACT

Therapeutic faradic current generators are used for stimulation of muscles and nerves of a body. Disclosed is such a generator in one embodiment having a unijunction transistor relaxation oscillator that feeds a Schmitt trigger, the output of which gates a power oscillator. The power oscillator drives a pair of electrodes that are put in contact with the skin.

1 Claim, 1 Drawing Figure

